

UYGULAMALAR

Düzenli hava akışı istenen steril odalar
Temiz odalar ve ameliyat odaları.

APPLICATIONS

Steril rooms where laminar air flow is required.
Clean rooms and operating theatres.



EN 779 CLASS	F6	F7	F8
Average Efficiency Em%	60-80	80-90	90-95
Recommended Final Pressure Drop	450 Pa	450 Pa	450 Pa
Max. Final Pressure Drop	800 Pa	800 Pa	800 Pa
Continuous Temperature Resistance	80 C	80 C	80 C
Max. Relative Humidity Resistance	100%	100%	100%
Frame	Plastic, Galvanized	Plastic, Galvanized	Plastic, Galvanized
Media	Microfine glass media in a mini pleat design		

SINIFI	ÖLÇÜ	DEBİ	İLK BASINÇ	YÜZEY ALANI
Class	Dimensions	Flow Rate	Initial Pressure Drop	Media Area
En 779	mm	m3/h	Pa	m2
F6	287*592*130	1700	90	5,80
F6	490*592*130	2850	90	10,60
F6	592*592*130	3400	90	13,30
F6	287*592*130	1700	135	3,00
F6	490*592*130	2850	135	5,50
F6	592*592*130	3400	135	7,00
F7	287*592*130	1700	120	5,80
F7	490*592*130	2850	120	10,60
F7	592*592*130	3400	120	13,30
F7	287*592*130	1700	150	3,00
F7	490*592*130	2850	150	5,50
F7	592*592*130	3400	150	7,00
F8	287*592*130	1700	130	5,80
F8	490*592*130	2850	130	10,60
F8	592*592*130	3400	130	13,30
F8	287*592*130	1700	170	3,00
F8	490*592*130	2850	170	5,50
F8	592*592*130	3400	170	7,00